

ACAAB Audible Alarm Beacon



Key Features:

- Alarm/siren offers 32 selectable sounds and volume control
- Include high intensity LEDs
- 8 flash patterns
- Typical working properties of polycarbonate are -40° to 250°F (-40°C to 121°C)
- Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).
- Designed to meet the requirements of IP54.

Product Overview:

Here is a highly effective way to provide a visual and/or audible indication of an alarm. The combination of alarm and super bright flashing LEDs offer excellent protection for an array of circumstances as they draw attention in a hurry. The sirens and strobes will work in conjunction with our Merlin control panels. For other applications contact AGS Controls for additional technical information.

Technical Specifications:

General	Installation
Model	ACAAB
Operating Voltage	12VDC-24VDC
Operating Current	0.42A@12VDC, 0.22A@24VDC
Operating Temperature	-4°F - 140°F
Volume @1 foot	High 105dB, Low 85dB
8 Flash Patterns	Yes
Strobe Speed Control	No
32 Sounds	Yes
Strobe Only Control	Yes
Sound Only Control	Yes
Alarm Trigger	Trigger on power
Lens Tamper	N.C. 12VDC, 50mA Dry Contact
IP Rating	IP54

Construction

- ✓ Durable, polycarbonate construction.

Installation

- ✓ Operating environment temperatures for ACAAB models -4 °F to 140 °F (-20° C to 40 °C)

Electronics

- ✓ 12-24VDC power supply.

Options

- ✓ Available with amber, green, blue, red, white, lens.